



Index

| | | | |
|--|-----------------|---|--------------------|
| [A] Accuracy tolerance | 1-22 | Explanation of the property terms (of substances to be measured) | 4-20 |
| Airtec Tube | 3-10 | Explanation of the specification items (of Gastec detector tubes) | 2-2 |
| ANSI/ISEA | 1-34 | Explosive range | 2-6, 7-4 |
| Automatic Gas Sampler (AGS-1) | 3-65 | Extension Hoses(No.350A, 350A-10) | 1-11 |
| [B] Boiling point | 7-3 | Extension Sampling Pole (No.350BP-2). | 1-10 |
| Boring method | 1-46, 5-3 | [F] Flash point | 7-3 |
| BS | 1-35 | Filling reagents | 1-18 |
| [C] Calibration curve | 1-37 | Fluctuation of dust concentrations | 1-30 |
| Calibration gas generation | 1-37 | [G] Gas leakage inspection | 1-28 |
| Calibration gas generation methods | 1-38 | Gas sampling methods | 1-46 |
| Calibration gas generators | | Gastec applied detector tube systems for ground or water analysis | 5-1 |
| (Gastec Permeaters) | 5-6 | Gastec applied detector tube systems for long-term gas and vapour analysis | 4-1 |
| Calibration line | 1-36 | Gastec applied detector tube systems for short-term gas and vapour analysis | 3-1 |
| Calibration scale | 1-6, 1-16 | Gastec detector tube systems | 6, 1-44 |
| Capillary method | 1-47, 5-13 | Gastec detector tube technology | 6 |
| Coefficient of variation (CV) | 1-22 | Gastec environmental analysis technology | 1-44 |
| Coexisting substances and their interferences. | 2-5 | Gastec measurement support systems | 5-5 |
| Colour change | 2-4 | Gastec Permeaters | |
| Colour change layer | 1-21 | (Gastec PD-1 B Permeater, Gastec PD-1 B-2 Permeater) | 5-6 |
| Compound reaction | 1-23 | Gastec Polytec System | |
| Consultation service | 1-42 | (Qualitative Analysis System for Multiple Gases) | 3-24 |
| Correction factor | 2-3 | Gastec Pyrotec System | |
| Correction for atmospheric pressure | 1-26 | (Pyrotec Pyrolyzer System) | 3-2 |
| Correction for humidity | 1-26, 2-4 | Gastec quality control | 1-40 |
| Correction for temperature | 1-24, 2-4 | Gastec SG System | |
| Counterling (for multiple pump strokes) | 1-8 | (Smoke and Exhaust Gas Analysis System) | 3-10 |
| [D] Detecting limit | 2-4 | Gastec standard detector tubes | 1-4, 1-6, 1-9, 2-1 |
| Detecting reagents | 1-18 | Gastec Standard Detector Tube System | 6, 1-1 |
| Detector tube | | basic configuration | 1-2 |
| name | 1-16, 2-3 | options | 1-10 |
| number | 1-6, 1-16, 1-20 | structure | 1-4 |
| package | 1-2 | Gastec TG-1 System | |
| preparation | 1-12 | (Toxic Gas Detection System) | 3-30 |
| reading | 1-14 | Gastec WPT-132, WPT-133 and WPT-135 Systems (Water Pollutant Analysis Systems) | 5-9 |
| storage and disposal | 1-27 | Ground Pollutant Analysis System | 5-2 |
| Detector tube method | 4 | guide line (—), guide mark (▷) | 1-8 |
| Detector tubes affected by humidity | 1-26 | [H] Hazardous properties | |
| Detector tube technology (at Gastec) | 6 | (of substances to be measured) | 7-4 |
| Diffusion method (gas sampling) | 1-46 | Hermetic sealing | 1-40 |
| Diffusion tubes | 1-39, 6-5 | | |
| Diffusion tube method | | | |
| (calibration gas generation) | 1-39 | | |
| DIN | 1-35 | | |
| Direct reaction | 1-23 | | |
| Dosi-tubes | 4-2 | | |
| Dynamic dilution method | | | |
| (calibration gas generation) | 1-39 | | |
| [E] Expiration date | 1-17 | | |

| | | | |
|---|-----------|---|-----------|
| High-Precision Calibration Gas Generators (Gastec Permeaters) | 5-6 | Permeation tube method (calibration gas generation) | 1-38 |
| High-pressure gas cylinder method (calibration gas generation) | 1-39 | Physical adsorption (influence of temperatures) | 1-25 |
| I Influences of temperatures | 1-25 | Polytec I (No.107) | 3-25 |
| Information (on the detector tube package label) | 1-16 | Polytec II (No.25) | 3-26 |
| Information service | 1-42 | Polytec III (No.26) | 3-27 |
| Injection method (gas sampling) | 1-46 | Polytec IV (No.27) | 3-28 |
| Injection-type detector tubes | 3-35 | Pyrotec Pyrolyzer System (Gastec Pyrotec System) | 3-2 |
| Injection-Type Gas Measurement Systems (No. 600 and No. 610) | 3-34 | Pretreatment reagents | 1-18 |
| Interferences | 1-23 | Properties of substances to be measured | 7-1 |
| International standards on detector tubes | 1-34 | Pyrotec (No.840) | 3-2 |
| IUPAC | 1-35 | Pyrotubes | 3-3 |
| J JIS | 1-34 | Q QC No. (quality control number) | 1-6 |
| L Long-term gas and vapour analysis | 4-1 | Qualitative Analysis System for Multiple Gases (Gastec Polytec System) | 3-24 |
| M Measurements with the Gastec Standard Detector Tube System | 1-12 | Quality assurance program at Gastec | 1-36 |
| of concentrations within equipment or pipelines | 1-29 | R Random errors | 1-22 |
| timing and frequency | 1-30 | Reaction principles and interferences | 1-23 |
| tips | 1-28 | Reaction rate (influence of temperatures) | 1-25 |
| Measuring range | 1-16, 2-3 | Reagent adding method (gas sampling) | 1-46, 5-6 |
| Measuring range, extension | 1-21 | Relative standard deviation | 1-22, 2-4 |
| Measuring time | 2-4 | Rubber inlet | 1-7 |
| Model GV-100S Gas Sampling Pump | 1-5 | S Sampling | 1-13 |
| kit | 1-2 | at closed places | 1-18 |
| maintenance | 1-15 | completion (confirmation) | 1-13 |
| Molecular weight | 7-3 | into sampling bag | 1-29 |
| Motor-driven pump method (gas sampling) | 1-46 | into sampling bottle | 1-29 |
| N No.330 Sulphides Measurement System | 5-5 | time | 1-13, 2-4 |
| No.340 Hot Probe | 1-11 | SEI | 1-33 |
| No.345A Hot Probe Holder | 1-11 | Shelf life (of detector tubes) | 2-4 |
| No.350A Extension Hose | 1-11 | Single tube | 1-9 |
| No.350A-10 Extension Hose | 1-11 | Special measurement methods for ground or water pollutant analysis | 1-46 |
| No.350BP-2 Extension Sampling Pole | 1-10 | Specification items (of Gastec standard detector tubes) | 2-2 |
| No.357 Tube Holder | 1-11 | Specific gravity | 7-3 |
| No.361 Boring Pole Kit | 5-2 | Standard (number of) pump strokes | 1-6, 1-21 |
| No.500 Smoke Tester Kit | 6-8 | Standard sample volume | 1-21 |
| No.600 and No.610 Injection-Type Gas Measurement Systems | 3-34 | Static dilution method (calibration gas generation) | 1-39 |
| No.721 Tube Tip Holder | 1-10 | Stroke guide rings | 1-8 |
| No.840 Pyrotec | 3-2 | Sulphide ion detector tubes | 5-13 |
| Number of pump strokes | 1-13, 2-3 | Sulphides Measurement System (No.330) | 5-5 |
| O One Hand Operation Adapter Model GV-700 | 1-10 | Systematic errors | 1-22 |
| P Permeation tubes | 1-38, 6-4 | T Testing service | 1-42 |
| | | Threshold limit values (TLV-C, TLV-TWA, TLV-STEL) | 2-6 |
| | | Tips for detector tube reading | 1-14 |

| | |
|--|-----------|
| Tips for measurements | 1-28 |
| TLVs(TWA, STEL,C). | 7-4 |
| Total sulfide detector tubes | 5-6 |
| Toxic Gas Detection System | |
| (Gastec TG-1 System) | 3-30 |
| Trouble shooting | 9-2 |
| Tube temperature and sample temperature | 1-25 |
| Tube tip breaker | |
| (of the Model GV-100 Gas Sampling Pump) . | 1-7 |
| Tube Tip Holder (No.721) | 1-10 |
| TWA Measurement System | 4-2 |
| Twin tube. | 1-9 |
| Two-step reaction | 1-23 |
| <input type="checkbox"/> Units of concentrations | 1-31 |
| User services. | 1-42 |
| <input checked="" type="checkbox"/> Vacuum method (gas sampling) | 1-46 |
| Vapour density | 7-4 |
| Vapour-liquid equilibrium method | |
| (gas sampling) | 1-46, 5-9 |
| Vapour pressure | 7-3 |
| <input checked="" type="checkbox"/> Water Pollutant Analysis Systems | |
| (Gastec WPT-132, WPT-133 and WPT-135 | |
| Systems) | 5-9 |

MEMO

A series of horizontal dashed lines for writing.

For all types of gas and vapour SINCE 1970



GASTEC CORPORATION

8-8-6 Fukayanaka, Ayase-shi, Kanagawa 252-1195, Japan

Tel: +81(0)467-79-3910 Fax: +81(0)467-79-3979

URL: <http://www.gastec.co.jp/>



NEXTTEQ[®]

NEXTTEQ LLC

8406 BENJAMIN RD, SUITE J

TAMPA, FL 33634 USA

TEL: 877-312-2333

FAX: 877-312-2444

WWW.NEXTTEQ.COM

NEXTTEQ IS GASTEC'S EXCLUSIVE
U.S. MASTER WHOLESALE DISTRIBUTOR.