

Technical Information
Material Safety Data Sheet

SDT-103_03E

SECTION 1		CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
MANUFACTURE'S NAME GASTEC CORPORATION	TELEPHONE NUMBER +81-467-79-3910	FACSIMILE NUMBER +81-467-79-3979	
ADDRESS 6431 Fukaya, Ayase-City, Kanagawa 252-1103, Japan			
REFERENCE NUMBER SDT-103_03E	DATE PREPARED June 28, 2005		
PRODUCT NAME	Gas Detector Tube Hydro Carbons Lower Class Tube No.103		
SECTION 2		COMPOSITION/INFORMATION ON INGREDIENTS	
Detctor Tube: Porous Silica Gel (0.9g) impregnated with Fuming Sulfuric Acid (20-25%) and Chromic Anhydride (<5%) in a glass tube. Aftertreatment Tube: Porous Silica Gel (0.3g) impregnated in a glass tube.			
SECTION 3		HAZARDOUS IDENTIFICATION	
Not applicable			
SECTION 4		FIRST AID MEASURES	
Eye contact:	Wash eyes immediately with plenty of water for at least 15 minutes and see a doctor.		
Skin contact:	Wash affected area immediately with soap and plenty of water.		
Inhalation:	Not applicable		
Ingestion:	Rinse mouth immediately and see a doctor.		
SECTION 5		FIRE FIGHTING MEASURES	
None			
SECTION 6		ACCIDENTAL RELEASE MEASURES	
Not applicable			
SECTION 7		HANDLING AND STORAGE	
When breaking off the tube ends, keep away from eyes. Broken glass tubes should not be picked up with bare hands. Tubes should be stored in a cool and dark place.			
SECTION 8		EXPOSURE PROTECTION	
Not applicable			
SECTION 9		PHYSICAL AND CHEMICAL PROPERTIES	
Fuming sulfuric acid, Chromic anhydride:			
Flash point:	Not available		
Autoignition point:	Not available		

SECTION 10 STABILITY AND REACTIVITY

Fuming sulfuric acid:	
Stability:	White smoke poisonous gas (sulfur trioxide) is emitted in air.
Reactivity:	React violently with water to evolve heat. Diluted sulfuric acid reacts with metals such as iron to form flammable hydrogen gas may cause fire and explosion. May cause ignition in contact with organic materials.
Condition to avoid:	Sunlight, Heat, Moisture
Hazardous decomposition product:	Sulfur oxides may be formed.
Chromic anhydride:	
Stability:	Stable.
Reactivity:	Strong oxidizers. Contact with organic agents or metal powder may cause expose by heat or shock. Contact with organic agents may cause fire.
Condition to avoid:	Sunlight, Heat
Hazardous decomposition product:	Not available

SECTION 11 TOXICOLOGICAL INFORMATION

Fuming sulfuric acid:	
Acute toxicity data:	LC50 (ihl, rat): 347ppm/1H (RTECS)
Irritation data:	as Sulfuric acid; Eye; rabbit; 250 μ g; severe (RTECS)
Mutagenicity:	Not available
Carcinogen:	IARC: Human carcinogen (Group 1) ACGIH: as Sulfuric acid; Suspected human carcinogen (A2)
Chromic anhydride:	
Acute toxicity data:	LD50 (ip, rat): 58400 μ g/kg (RTECS) LD50 (iv, rat): 9260 μ g/kg (RTECS) LD50 (orl, mouse): 127mg/kg (RTECS) LD50 (ip, mouse): 14mg/kg (RTECS) LDLo (sc, mouse): 20mg/kg (RTECS) LD50 (iv, mouse): 17100 μ g/kg (RTECS)
Irritation data:	Not available
Mutagenicity:	Not available
Carcinogen:	as Hexavalent chromium; NTP: K (Prospective human carcinogen) IARC: Group 1 (Human carcinogen) ACGIH: A1 (Known to be carcinogen) Japan Society for Occupational Health: Group 1 (Human carcinogen)

SECTION 12 ECOLOGICAL INFORMATION

Fuming sulfuric acid:	Not available
Chromic anhydride:	
Biodegradability:	Not available
Bioaccumulation Potential:	Concentration scale factor (BCF); 4.6-15 (concentration, 100 μ g/l); 14-21 (concentration, 20 μ g/l); 11-43 (concentration 5 μ g/l); 16-72 (concentration 94-242 μ g/l)
Aquatic toxicity:	LC50 (killifish): 82mg/l/48H

SECTION 13 DISPOSAL CONSIDERATION

The detector tube contains 12.22mg of hexavalent chromium. Dispose of in accordance with all applicable laws and regulations. (Contact local environmental agency for specific rules.)

SECTION 14	TRANSPORT INFORMATION Breakage of tubes caused by drops, high pressure or bends should be avoided.
SECTION 15	REGULATORY INFORMATION Not applicable
SECTION 16	OTHER INFORMATION No specific notes