

**Technical Information**  
**Material Safety Data Sheet**

SDT-112\_04E

<b>SECTION 1</b>		<b>CHEMICAL PRODUCT AND COMPANY IDENTIFICATION</b>	
<b>MANUFACTURE'S NAME</b>	<b>TELEPHONE NUMBER</b>	<b>FACSIMILE NUMBER</b>	
GASTEC CORPORATION	+81-467-79-3910	+81-467-79-3979	
<b>ADDRESS</b>			
8-8-6 Fukayanaka, Ayase-City, Kanagawa 252-1195, Japan			
<b>REFERENCE NUMBER</b>		<b>DATE PREPARED</b>	
SDT-112_04E		May 31, 2006	
<b>PRODUCT NAME</b>	Gas Detector Tube Ethyl Alcohol Detector Tube No. 112		
<b>SECTION 2</b>		<b>COMPOSITION/INFORMATION ON INGREDIENTS</b>	
Porous Silica Gel (0.7 g) impregnated with Sulfuric Acid (<5%) and Potassium Bichromate (<1%) in a glass tube.			
<b>SECTION 3</b>		<b>HAZARDOUS IDENTIFICATION</b>	
Not applicable			
<b>SECTION 4</b>		<b>FIRST AID MEASURES</b>	
Eye contact:	Wash eyes immediately with plenty of water for at least 15 minutes and see a doctor.		
Skin contact:	Wash affected area immediately with soap and plenty of water.		
Inhalation:	Not applicable		
Ingestion:	Rinse mouth immediately and see a doctor.		
<b>SECTION 5</b>		<b>FIRE FIGHTING MEASURES</b>	
None			
<b>SECTION 6</b>		<b>ACCIDENTAL RELEASE MEASURES</b>	
Not applicable			
<b>SECTION 7</b>		<b>HANDLING AND STORAGE</b>	
When breaking off the tube ends, keep away from eyes. Broken glass tubes should not be picked up with bare hands. Tubes should be stored in a cool and dark place.			
<b>SECTION 8</b>		<b>EXPOSURE PROTECTION</b>	
Not applicable			
<b>SECTION 9</b>		<b>PHYSICAL AND CHEMICAL PROPERTIES</b>	
Sulfuric acid:			
Flash point:	Not available		
Autoignition point:	Not available		

---

**SECTION 10**                      **STABILITY AND REACTIVITY**

Sulfuric acid:

Stability:

Stable. Absorb moisture powerfully from the air.

Reactivity:

React violently with water to evolve heat and may spatter. Bite into metals and concrete caused by oxidation. Carbonize to flammable organic materials.

Condition to avoid:

Sunlight, Heat, Moisture

Material to avoid:

Organic materials, Reducing agents, Metals

Hazardous decomposition product:

Sulfur oxides may be formed

---

**SECTION 11**                      **TOXICOLOGICAL INFORMATION**

Sulfuric acid

Acute toxicity data:

LD50 (orl, rat): 2140mg/kg

LC50 (ihl, cavy): 18mg/m<sup>3</sup>

Irritation data:

Eye; rabbit; 1380µg; severe

Mutagenicity:

Not available

Carcinogen:

Not available

---

**SECTION 12**                      **ECOLOGICAL INFORMATION**

Not available

---

**SECTION 13**                      **DISPOSAL CONSIDERATION**

This tube contains 1.77 mg of hexavalent chromium.

Dispose of in accordance with all applicable laws and regulations.

(Contact local environmental agency for specific rules.)

---

**SECTION 14**                      **TRANSPORT INFORMATION**

Breakage of tubes caused by drops, high pressure or bends should be avoided.

---

**SECTION 15**                      **REGULATORY INFORMATION**

Not applicable

---

**SECTION 16**                      **OTHER INFORMATION**

No specific notes