

Technical Information
Material Safety Data Sheet

SDT-131L_05E

SECTION 1		CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
MANUFACTURE'S NAME GASTEC CORPORATION	TELEPHONE NUMBER +81-467-79-3910	FACSIMILE NUMBER +81-467-79-3979	
ADDRESS 8-8-6 Fukayanaka, Ayase-City, Kanagawa 252-1195, Japan			
REFERENCE NUMBER SDT-131_05E		DATE PREPARED April 16, 2009	
PRODUCT NAME	Gas Detector Tube Vinyl Chloride Detector Tube No. 131L		
SECTION 2		COMPOSITION/INFORMATION ON INGREDIENTS	
Pretreatment Tube: Porous Silica Gel (0.7 g) impregnated with Sulfuric Acid (<25-45%) and Potassium Dichromate (<1%) in a glass tube. Detector Tube: Porous Silica Gel (0.5g) impregnated in a glass tube.			
SECTION 3		HAZARDOUS IDENTIFICATION	
Not applicable			
SECTION 4		FIRST AID MEASURES	
Eye contact:	Wash eyes immediately with plenty of water for at least 15 minutes and see a doctor.		
Skin contact:	Wash affected area immediately with soap and plenty of water.		
Inhalation:	Not applicable		
Ingestion:	Rinse mouth immediately and see a doctor.		
SECTION 5		FIRE FIGHTING MEASURES	
None			
SECTION 6		ACCIDENTAL RELEASE MEASURES	
Not applicable			
SECTION 7		HANDLING AND STORAGE	
When breaking off the tube ends, keep away from eyes. Broken glass tubes should not be picked up with bare hands. Tubes should be stored in a refrigerator.			
SECTION 8		EXPOSURE PROTECTION	
Not applicable			
SECTION 9		PHYSICAL AND CHEMICAL PROPERTIES	
Sulfuric acid:			
Flash point:	Not available		
Autoignition point:	Not available		

SECTION 10 STABILITY AND REACTIVITY

Sulfuric acid:

Stability:

Reactivity:

Stable. Absorb moisture powerfully from the air.

React violently with water to evolve heat and may spatter. Bite into metals and concrete caused by oxidation. Carbonize to flammable organic materials.

Condition to avoid:

Sunlight, Heat, Moisture

Material to avoid:

Organic materials, Reducing agents, Metals

Hazardous decomposition product:

Sulfur oxides may be formed

SECTION 11 TOXICOLOGICAL INFORMATION

Sulfuric acid

Acute toxicity data: LD50 (orl, rat): 2140mg/kg
LC50 (ihl, cavy): 18mg/m³

Irritation data: Eye; rabbit; 1380 μ g; severe

Mutagenicity: Not available

Carcinogen: Not available

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATION

This pretreatment tube contains 0.13 mg of hexavalent chrome. Dispose of in accordance with all applicable laws and regulations. (Contact local environmental agency for specific rules.)

SECTION 14 TRANSPORT INFORMATION

Breakage of tubes caused by drops, high pressure or bends should be avoided.

SECTION 15 REGULATORY INFORMATION

Not applicable

SECTION 16 OTHER INFORMATION

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.