

Technical Information
Material Safety Data Sheet

SDT-133LL_04E

SECTION 1		CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
MANUFACTURE'S NAME GASTEC CORPORATION	TELEPHONE NUMBER +81-467-79-3910	FACSIMILE NUMBER +81-467-79-3979	
ADDRESS 8-8-6 Fukayanaka, Ayase-City, Kanagawa 252-1195, Japan			
REFERENCE NUMBER SDT-133LL_04E	DATE PREPARED May 31, 2006		
PRODUCT NAME	Gas Detector Tube Tetrachloroethylene Detector Tube No.133LL		
SECTION 2		COMPOSITION/INFORMATION ON INGREDIENTS	
Porous Silica Gel (0.7g) impregnated with Sulfuric Acid (5-15%) and Lead Dioxide (<5%) in a glass tube.			
SECTION 3		HAZARDOUS IDENTIFICATION	
Not applicable			
SECTION 4		FIRST AID MEASURES	
Eye contact:	Wash eyes immediately with plenty of water for at least 15 minutes and see a doctor.		
Skin contact:	Wash affected area immediately with soap and plenty of water.		
Inhalation:	Not applicable		
Ingestion:	Rinse mouth immediately and see a doctor.		
SECTION 5		FIRE FIGHTING MEASURES	
None			
SECTION 6		ACCIDENTAL RELEASE MEASURES	
Not applicable			
SECTION 7		HANDLING AND STORAGE	
When breaking off the tube ends, keep away from eyes. Broken glass tubes should not be picked up with bare hands. Tubes should be stored in a refrigerator.			
SECTION 8		EXPOSURE PROTECTION	
Not applicable			
SECTION 9		PHYSICAL AND CHEMICAL PROPERTIES	
Lead dioxide, Sulfuric acid:			
Flash point:	Not available		
Autoignition point:	Not available		

SECTION 10 STABILITY AND REACTIVITY

Lead dioxide:
Stability: Stable. Oxygen is emitted when heated.
Reactivity: Not available
Condition to avoid: Sunlight, Heat
Hazardous decomposition product: Lead chloride and trilead tetroxide may be formed.

Sulfuric acid:
Stability: Stable. Absorb moisture powerfully from the air.
Reactivity: React violently with water to evolve heat and may spatter. Bite into metals and concrete caused by oxidation. Carbonize to flammable organic materials.
Condition to avoid: Sunlight, Heat, Moisture
Material to avoid: Organic materials, Reducing agents, Metals
Hazardous decomposition product: Sulfur oxides may be formed

SECTION 11 TOXICOLOGICAL INFORMATION

Lead dioxide:
Acute toxicity data: LD50 (ip, cavy): 220mg/kg (RTECS)
Irritation data: Not available
Mutagenicity: Not available
Carcinogen: IARC: Possibility human carcinogen (Group 2B)
JSOH: Possibility human carcinogen (Group 2B) (no sufficient basis)

Sulfuric acid:
Acute toxicity data: LD50 (orl, rat): 2140mg/kg
LC50 (ihl, cavy): 18mg/m³
Irritation data: Eye; rabbit; 1380µg; severe
Mutagenicity: Not available
Carcinogen: Not available

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATION

This tube contains 6.40mg of lead.
Dispose of in accordance with all applicable laws and regulations.
(Contact local environmental agency for specific rules.)

SECTION 14 TRANSPORT INFORMATION

Breakage of tubes caused by drops, high pressure or bends should be avoided.

SECTION 15 REGULATORY INFORMATION

Not applicable

SECTION 16 OTHER INFORMATION

No specific notes