

Technical Information
Material Safety Data Sheet

SDT-137_04E

| | | | |
|--|--|--|--|
| SECTION 1 | | CHEMICAL PRODUCT AND COMPANY IDENTIFICATION | |
| MANUFACTURE'S NAME GASTEC CORPORATION | TELEPHONE NUMBER +81-467-79-3910 | FACSIMILE NUMBER +81-467-79-3979 | |
| ADDRESS 8-8-6 Fukayanaka, Ayase-City, Kanagawa 252-1195, Japan | | | |
| REFERENCE NUMBER SDT-137_04E | | DATE PREPARED April 16, 2009 | |
| PRODUCT NAME | Gas Detector Tube Chloroform Tube No.137 | | |
| SECTION 2 | | COMPOSITION/INFORMATION ON INGREDIENTS | |
| Pretreatment Tube: Porous Silica Gel (0.9g) impregnated with Fuming Sulfuric Acid (40-50%) and Chromic Anhydride (<1%) in a glass tube. Detector Tube: Porous Silica Gel (0.4g) impregnated with Sulfuric Acid (<1%), Chromic Anhydride (<1%) and O-Tolidine (<0.1%) in a glass tube. | | | |
| SECTION 3 | | HAZARDOUS IDENTIFICATION | |
| Not applicable | | | |
| SECTION 4 | | FIRST AID MEASURES | |
| Eye contact: | Wash eyes immediately with plenty of water for at least 15 minutes and see a doctor. | | |
| Skin contact: | Wash affected area immediately with soap and plenty of water. | | |
| Inhalation: | Not applicable | | |
| Ingestion: | Rinse mouth immediately and see a doctor. | | |
| SECTION 5 | | FIRE FIGHTING MEASURES | |
| None | | | |
| SECTION 6 | | ACCIDENTAL RELEASE MEASURES | |
| Not applicable | | | |
| SECTION 7 | | HANDLING AND STORAGE | |
| When breaking off the tube ends, keep away from eyes. Broken glass tubes should not be picked up with bare hands. Tubes should be stored in a cool and dark place. | | | |
| SECTION 8 | | EXPOSURE PROTECTION | |
| Not applicable | | | |
| SECTION 9 | | PHYSICAL AND CHEMICAL PROPERTIES | |
| Fuming sulfuric acid: | | | |
| Flash point: | Not available | | |
| Autoignition point: | Not available | | |

SECTION 10 STABILITY AND REACTIVITY

Fuming sulfuric acid:

Stability: White smoke poisonous gas (sulfur trioxide) is emitted in air.

Reactivity: React violently with water to evolve heat. Diluted sulfuric acid reacts with metals such as iron to form flammable hydrogen gas may cause fire and explosion. May cause ignition in contact with organic materials.

Condition to avoid: Sunlight, Heat, Moisture

Hazardous decomposition product: Sulfur oxides may be formed.

SECTION 11 TOXICOLOGICAL INFORMATION

Fuming sulfuric acid:

Acute toxicity data: LC50 (ihl, rat): 347ppm/1H (RTECS)

Irritation data: as Sulfuric acid; Eye; rabbit; 250 μ g; severe (RTECS)

Mutagenicity: Not available

Carcinogen: IARC: Human carcinogen (Group 1)

ACGIH: as Sulfuric acid; Suspected human carcinogen (A2)

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATION

The pretreatment tube contains 1.73mg of hexavalent chromium. The detector tube contains 1.21mg of hexavalent chromium. Dispose of in accordance with all applicable laws and regulations. (Contact local environmental agency for specific rules.)

SECTION 14 TRANSPORT INFORMATION

Breakage of tubes caused by drops, high pressure or bends should be avoided.

SECTION 15 REGULATORY INFORMATION

Not applicable

SECTION 16 OTHER INFORMATION

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.